

BendixKing



AeroVue™ Touch

Experience Industry-Leading Flight Display

Your Solution for Certified Aircraft.

AeroVue™ Touch is a low-cost display available for 353 aircraft types that offers powerful and intuitive touchscreen capabilities with the highest screen resolution on the market today. The system delivers improved safety by consolidating all essential flight information onto one screen, and reduces pilot workload by making all flight-critical functions accessible with only one or two touches on the screen. The AeroVue Touch comes standard with industry-leading SmartView™ synthetic vision system, ADS-B In traffic and weather display.



Primary Flight Display

Characteristics	Specification
Dimensions	6.897 x 10.45 x 4.08 in. (175.18 x 265.43 x 103.63 mm)
Mounting Information	Front mount
Weight	7.59 lbs. (3.44 kg)
Current Draw	Typical: 1.33 AMP for 28 VDC 2.66 AMP for 14 VDC
Operating Voltage	9.0 to 30.3 VDC
Circuit Breaker	2 AMP for 28 VDC, 3 AMP for 14 VDC
Cooling	Convection cooled (no fan)
Connectors	1 female 78-pin and 1 male 78-pin
Viewing Angle Envelope	80° from all directions

Control Panel

Characteristics	Specification
Dimensions	1.48 x 6.25 x 3.67 in. (37.6 x 158.8 x 93.2 mm)
Mounting Information	Front mount
Weight	1.05 lbs. (0.47 kg)
Current Draw	Powered from flight display. Current draw included with flight display
Operating Voltage	Provided by flight display
Circuit Breaker	None, uses circuit breaker for flight display
Cooling	Convection cooled (no fan)
Connectors	Male 9-pin D-Sub

Find Out More

To learn more, call 1.855.250.7027, contact your local BendixKing dealer or visit bendixking.com

BendixKing

9201-B San Mateo Blvd. NE
Albuquerque, NM 87113
BendixKing.com

Magnetometer

Characteristics	Specification
Dimensions	3.70 x 5.83 x 1.33 in. (93.98 x 148.08 x 37.78 mm)
Weight	0.90 lbs. (0.41 kg)
Temperature	-55 °C to +70 °C
Altitude	55,000 ft.
Operating Voltage	9.0 to 30.3 VDC
Current Draw (at 27.5 VDC)	80 mA Nominal, 25 °C, after 2 minute warmup 200 mA Nominal, -55 °C, after 2 minute warmup 700 mA Maximum, -55 °C
Circuit Breaker	1 AMP for 28 VDC, 2 AMP for 14 VDC
Signal Inputs/Outputs	Serial CAN bus
Cooling	Convection cooled (no fan)
Connector	Female 9-pin

Air Data Attitude Heading Reference System (ADAHRS)

Characteristics	Specification
Dimensions	8.65 x 5.1 x 1.4 in. (219.72 x 129.43 x 35.56 mm)
Weight	2.17 lbs. (0.98 kg)
Current Draw	Typical: 0.2 AMP for 28 VDC 0.4 AMP for 14 VDC
Operating Voltage	9.0 to 30.3 VDC
Circuit Breaker	2 AMP for 28 VDC, 3 AMP for 14 VDC
Cooling	Convection cooled (no fan)
Connectors	Male 50-pin and Female 9-pin (maintenance port)

Outside Air Temperature Probe (OAT)

Characteristics	Specification
Dimensions	1.65 x 1.75 x 1.00 in. (41.91 x 44.45 x 25.4 mm)
Weight	0.15 lbs. (0.07 kg)
Current Draw	None, no interface to aircraft power
Operating Voltage	None, connected to ADAHRS, no interface to aircraft power
Circuit Breaker	None
Cooling	No cooling required
Connectors	5 ft. 3-conductor shielded wire lead, spliced into wiring harness

Database Upload: Over Wi-Fi and USB-C